

# EVINRUDE®



# 3.5 HP/2.5 kW



## SPECIFICATIONS

|                                   |   |
|-----------------------------------|---|
| ENGINE TYPE                       | 1-CYLINDER/4-STROKE   |
| BORE X STROKE MM (IN)             | 55 X 36 (2.17 X 1.42)   |
| DISPLACEMENT CC (CU IN)           | 85.5 (5.2)  |
| GEAR RATIO                        | 2.15:1  |
| FULL THROTTLE RPM RANGE           | 5,000 - 6,000 RPM   |
| WEIGHT KG (LBS)*                  | 18 (41)*  |
| STARTING                          | MANUAL  |
| OIL TYPE                          | NMMA CERTIFIED FC-W® 4-STROKE OIL<br>SAE 10W-30/40 (SF, SG, SH, SJ) |
| OIL CAPACITY ML (FL. OZ.)         | 300 (10)  |
| FUEL TANK L                       | INTEGRAL TANK<br>1  |
| PROPELLER SELECTION RANGE CM (IN) | 11.43-17.78 (4.5-7)   |
| ALTERNATOR OUTPUT                 | N/A   |
| STEERING                          | TILLER HANDLE   |
| TRIM METHOD                       | MANUAL<br>TILT  |
| SHAFT LENGTH MM (IN)              | 381 (15), 508 (20)  |
| WARRANTY                          | 3-YEAR, NON-DECLINING   |
| EMISSIONS COMPLIANCE              | CARB 3 STAR   |

\* Weight based on lightest model.